

PCTWORLD INTELLECTUAL PROPE
International Bu

INTERNATIONAL APPLICATION PUBLISHED UNDER

WO 9605279A1

(51) International Patent Classification ⁶ : C11B 7/00		A1	(11) International Publication Number: WO 96/05279
			(43) International Publication Date: 22 February 1996 (22.02.96)
(21) International Application Number: PCT/EP95/03035		(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG).	
(22) International Filing Date: 28 July 1995 (28.07.95)			
(30) Priority Data: 94306056.6 17 August 1994 (17.08.94) EP			
(34) Countries for which the regional or international application was filed: AT et al.			
(71) Applicant (for all designated States except US): QUEST INTERNATIONAL B.V. [NL/NL]; Huizerstraatweg 28, NL-1411 GP Naarden (NL).		Published With international search report.	
(72) Inventors; and (75) Inventors/Applicants (for US only): HARRIS, John, Bernard [GB/GB]; 20 Colworth Road, Sharnbrook, Bedford MK44 1ET (GB). KEULEMANS, Cornelius, Nicholaas, M. [NL/NL]; Zwanenburg 8, NL-3181 SV Rozenburg (NL). MILTON, Leslie, Alan [GB/NL]; Eemwijkplein 24, NL-2271 RB Voorburg (NL). ROEST, Erwin, J., G. [NL/NL]; Spijistraat 7, NL-1531 EA Wormer (NL).			
(54) Title: OIL MODIFICATION			
(57) Abstract			
A pseudo-steady state fractionation of a polymorphic fat, resulting in a product which is in a kinetically stable crystal form is performed in a way that a σ -value is maintained below 0.5, formula (I) wherein S_c being: the percentage solids in crystalliser at crystallisation temperature, S_E being: the percentage solids after stabilisation for 48 hrs at exit temperature of crystalliser.		$\sigma = 1 - \frac{S_c}{S_E} \quad (I)$	

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

OIL MODIFICATION

The dry fractionation processes for the fractionation of fats disclosed in the prior art are all based on the use of a system comprising a heat exchanger for the starting oil, a crystalliser for the oil obtained after the heat exchange and a filter press wherein crystals are separated from the liquid components.

- Because of the conditions applied during these known dry fractionation processes the products contain large amounts of kinetically unstable crystals. Moreover those known processes require high levels of undercooling, which make the processes difficult to control. As a result of above the products are not optimal for filtering, which results in poor yields and poor separation efficiency.

It would be very beneficial if a dry fractionation could be found, that does not have above drawbacks.

20

We have conducted a study in order to find out whether such a process could be developed. This study resulted in an economically feasible (semi-)continuous dry fractionation process for the crystallisation of polymorphic fat

- molecules. Therefore, our invention concerns a process for the crystallisation of polymorphic fat molecules in a pseudo-steady state process, wherein the crystallisation is performed in a dry fractionation system in such a way that the crystal form of the product is a kinetically-stable crystal form, while during the crystallisation a σ -value is maintained below 0.5, preferably below 0.3, more preferably between 0.001 and 0.2, during a period of at least 12 hrs, wherein :

35

$$\sigma = 1 - \frac{S_c}{S_E}$$

S_c being : percentage of solids in crystalliser at crystallisation temperature;

S_E being : percentage of solids after stabilisation for 48 hours at exit temperature of the crystalliser.

So in order to measure S_E a sample is taken from the crystalliser at time is 0 hrs and kept for 48 hrs at final crystalliser temperature without stirring. At time $t=48$ hours the percentage of solids in the sample is measured by NMR-pulse.

For the measurement of S_C the solids are measured in the crystalliser immediately before material is taken out for pressing.

Time $t=0$ hrs is taken as the point in time where for the first time material is taken from the crystalliser for pressing.

If S_C and S_E are very close it can be, that the values obtained (due to experimental inaccuracy) are such, that $S_E < S_C$, so that σ is negative.

$$\sigma = 1 - \frac{S_C}{S_E}$$

20

Above process according to our invention is conducted in such a way, that the system is always close to its equilibrium, therefore high levels of the more kinetically stable crystal form are obtained. The process is best achieved by performing a very slow stirring during the crystallisation step. Consequently the crystals are easier to filter and an optimal production in high yields and high separation efficiency can be achieved.

Kinetically stable crystal form being defined as any crystalform that at the process-conditions at steady-state does not change substantially during the process and thus may include the thermodynamically stable crystalform.

Another advantage is obtained by applying our novel process on polymorphic fats. The fats obtained according to our novel process do contain more of the stable β -crystals,

than the products of the conventional processes (which contain far more β^1 -crystals). Polymorphic fats being defined as fats, that can crystallise in different crystal-forms.

5

The above-mentioned process can be run as a pseudo-steady state process for more than 24 hours, preferably for more than 48 hours, while even a period of more than 60 hours can be achieved.

10

For the above-mentioned process to be carried out, a minimum residence time (τ) of the fat in the crystalliser should be maintained. Suitable residence times are τ of more than 1 hour, preferably more than 4 hours and more preferably more than 12 hours, residence time (τ) being defined as :

$$\tau = \frac{\text{Volume of crystalliser}}{\text{Average flow rate}}$$

Average flow rate being defined as: total volume of

20 material taken from the crystalliser during one experiment divided by the total time of the experiment (starting from $t=0$)

For the above-mentioned σ -values to be achieved, it is suitable to apply a crystalliser whose volume represents
25 more than 2 times, preferably more than 3 times, more preferably more than 5 times the filling (volume) of the separator applied. Very suitably, crystallisers are applied having a volume of more than 10 m³, preferably more than 30 m³, more preferably more than 60 m³.

30

Using the above-mentioned volumes for crystalliser and separator (= filter press) causes (considering the duration of the process) only a limited volume of pre-crystallised oil to be conveyed from the crystalliser to the filter
35 press. This increases the available time for residence of the oil in the crystalliser, thus making it possible, to come very close to the equilibrium-conditions.

Because of the above-mentioned condition, the fat separated as product will be in a kinetically-stable crystal form. This means that, when a polymorphic fat of the SOS-type triglycerides is applied, in this fat more than 25%, preferably more than 45%, more preferably more than 60% of the solid fat, can be present in the β -polymorphic crystal form.

Examples of fats that can be suitably applied are fats selected from the group consisting of palm oil, palm oil olein, shea, high-oleic sunflower oil, palm oil stearin, high stearic bean oil, hardened vegetable fat, enzymically interesterified fats, chemically interesterified fats or mixtures thereof.

A main advantage of the process according to the invention is that it can be controlled by selecting and adjusting the flow rate, shear rate and temperature only.

Typical conditions that can be applied for the dry fractionation of palm oil olein are, e.g. :

temperature of starting oil : 50°C

temperature of oil after heat exchange : < 20°C

temperature of oil at the end of crystalliser : < 15°C

temperature of oil in the filter press < 15 °C

flow rate in heat exchanger 6 m³/hr

flow rate in at least one of the crystallisers 3 m³/hr

volume of crystalliser 54 m³

volume of filter press 4 m³ (filling volume: 5-7 m³)

So : τ = 18 hours

S_i applied : 20-30%

S_E applied : 25-35 %

So : σ = remains between 0.14 and 0.25

Using the above-mentioned conditions, a standard palm oil olein can be split into a top fraction (yield 50 %) and into a bottom fraction (yield 50 %).

- 5 Such a process can be run for 60-70 hours without giving rise to problems of encrustation, slurry stability, polymorphic form or viscosity.

Example I

A dry-fractionated palm oil olein was used as starting material. This oil had an I.V.= 55.9; a solid fat content (NMR-pulse) at 20°C of 5.0 and contained 35.9 wt.% of SOS-
5 triglycerides. (S=saturated C₁₆ + C₁₈-fatty acids: O=oleic acid).

The oil was fractionated by bringing into a crystalliser with a volume of 10 l., which was stirred slowly (10 rpm).

10 The oil was cooled, using the following regime:

- 1 hr at 50°C
- from 50 to 31°C in 9 hrs
- 1 hr at 31°C
- from 31 to 29°C in 2 hrs
- 15 from 29 to 25°C in 40 hrs
- from 25 to 14°C in 11 hrs
- from 14 to 13.5°C in 5 hrs

Three pressings were performed. The amounts of materials
20 removed per pressing are shown in table I. After each removal the same amount of starting material was added to the crystalliser as liquid, at 13.5°C.

Pressing conditions were:

- 25 0-24 bar in 2 hrs (linear increase), followed by 1 hr at 24 bar. Presssing temperature in all experiments was the temperature in the crystalliser at the point in time when material was taken for pressing.

Table I

	#1	#2	#3
Time (h)	0	21.5	45.5
S _C %	23.3	22.2	25.7
5 S _E %	29.0	29.0	29.0
σ	0.20	0.23	0.11
10 weight of slurry removed per pressing (g)	455	457	452
τ (over 3 pressings) h	300		
15 Sep. Eff. in press %	49.6	51.1	50.3
Yield of stearin %	47.5	53.4	54.2
20 Quality of olein IV N0	64.2 8.6	66.4 5.4	67.6 3.6
25 Quality of stearin SOS (40h/20°C) N20	52.0 47.6	50.9 47.1	52.0 49.3

30 Both olein and stearin are of good quality.

Example 2

The stearin, obtained in example I was subjected to a dry
factionation. The following conditions were applied:

- 35 volume crystalliser: 10 l
stirrer at 10 r.p.m.
cooling program:
1 hr at 70°C
cooling from 70 to 30°C in 4 hrs.

cooling from 30 to 27.2°C in 4 hrs.

8 hrs. at 27.2°C

cooling from 27.2 to 26.2°C in 33 hrs.

Four pressings were performed. The amounts of materials removed and added per pressing are mentioned in table 2. The materials added had a temperature of 26.2°C.

Pressing conditions: 0-24 bar in 2 hrs.

1 hr at 24 bar

Press temperature in all experiments was the same as the temperature in the crystalliser at the point in time when material was taken for pressing.

Table 2

	#1	#2	#3	#4
Time(h)	0	24	48	72
S _c %	18.4	19.2	19.0	18.0
S _E %	21.1	21.1	21.1	21.1
σ	0.13	0.09	0.10	0.15
weight of slurry removed per pressing g	358	388	368	346
τ (over 4 pressings) h	450			
Sep. Eff. in press %	42.6	43.9	44.2	43.1
Yield of stearin	58.1	54.1	53.3	54.0
Quality of stearin SOS % (40h/26°) N 20	72.0 72.8	73.4 74.9	72.6 75.0	71.8 73.5
Quality of olein SOO	17.5	16.4	16.3	16.0

Both stearin and olein are of good quality.

Example 3

5 Example 2 was repeated. However, the σ -value was adjusted to $\sigma = 0.73$ by adding a sufficient amount of the fresh stearin having a temperature of 26.2°C . This was done by adding 1081 g of the fresh liquid stearin to 512 g of the oil # 4 with $\sigma = 0.15$.

10 The product after pressing was not good. The above example was continued. However, the temperature in the crystalliser was adjusted to 23.0°C , resulting in an S_c of 19.3% and a $\sigma = 0.09$. The moment material was taken for the press is now the time = 0.

15 The resulting product after pressing was again not good, the reason being that although σ was in the required range, the process time was less than 12 hours.

The results can be summarised as follows:

20

$t = 0$ hour at the time we did the pressing with $\sigma = \text{ca } 0.7$
Temp. in crystalliser = 26.2°C
Pressing 0-24 bar in 2 hours + 1 hour at 24 bar.
Temperature in press was also 26.2°C .

25

$t = 0$ hour at the time we did the pressing with $\sigma = \text{ca } 0.1$
Temp. in crystalliser = 23.0°C
Pressing 0-24 bar in 2 hours + 1 hour at 24 bar.
Temperature in the press was also 23.0°C .

30

Table 3

	#1	#2
time (h)	0	0
S_c %	5.8	19.3
S_E %	21.1	21.1
σ	0.73	0.09

35

weight of slurry removed g	416	360
τ h	7.5 (3 liter crystalliser)	28 (10 liter crystalliser)
Sep. Eff. in press %	18.9	38.2
Yield of stearin %	59.1	78.5
Quality of stearin SOS	62.9	64.0
40h/26°C N20	58.1	59.6
Quality of olein SOO	12.6	16.3

In both pressings the quality of stearin is not good. (SOS-levels and N_{20} are too low.).

Example 4

A palm oil stearin with:

IV= 31.8

Slip melting point= 51.3 °C

SSS= 33.3 %

was fractionated

Experimental details:

Volume crystalliser: 3 liter

Stirrer at 10 rpm

Cooling programme: 1 hour at 70°C

Cooling from 70--> 52 in 1 h

Cooling from 52--> 42 °C in 10 h

Four pressings were done. The amounts of material removed and added per pressing are shown in the table 4. The materials added as liquid had a temperature of 50°C, because for else the palm oil stearin is not liquid. Pressing : 0-24 bar in 1 hour, followed by 30 minutes at 24 bar. Temperature of pressing was 42°C.

Table 4

	#1	#2	#3	#4
Time (h)	0	24	48	120
S _C	14.1	14.8	15.2	15.9
S _E	14.7	14.7	14.7	14.7
σ	0.04	- 0.01	- 0.03	- 0.08
weight of slurry removed per pressing g	131	130	139	157
τ (Over 4 pressings) h	560			
Sep. Eff. in press	68.0	66.8	67.4	66.5
Yield of stearin	34.4	34.6	34.7	33.8
quality of stearin:C16	82.9	82.6	82.5	82.1
IV	10.8	9.6	9.9	10.1
mpt	59.8	59.6	59.6	59.1
quality of olein: S00	14.6	14.3	14.3	13.9

Both stearin and olein are of good quality.

30 Example 5

Hardened soybean oil, m.pt 39°C was fractionated into 2 fractions (a top-fraction A and an olein-fraction B).

The hardened soybean oil had the following N-values:

$$N_{20} = 68.6$$

$$N_{30} = 30.6$$

$$N_{35} = 10.9$$

Experimental details:

Volume crystalliser: 10 liter
stirrer at 10 rpm

Cooling programme: 1 hour at 70°C

Cooling from: 70--> 40° in 5 hours

Cooling from: 40--> 33° in 7 hours

- 5 The final temperature is decided by the quality of top fraction A.

Three pressings were done. The amounts of material removed and added per pressing are shown in the table 5. The materials added as liquid had a temperature of 40°C in order to ensure pourability.

Pressing: 0-24 bars in 2 hours+ 1 hour at 24 bar.

Press temperature: 33°C

15

Table 5

20

25

30

35

	# 1	#2	#3
Time (h)	0	24	44
S _C	13.3	12.6	14.1
S _E	13.3	13.3	13.3
σ	0	0.05	-0.06
weight of slurry removed per pressing g	469	505	453
τ (over 4 press.) h	290		
Sep. Eff. in press	76.4	71.2	70.0
Yield of A	20.5	22.2	24.7
Quality A:N ₃₅	75.1	72.8	69.5
slippoint	46.7	45.0	44.7
Quality of olein B: N ₂₀ -N ₃₅	53.3	53.1	51.4

Both A and B are of good quality.

Example 6

A palm olein-fraction, with the following analytical data, was fractionated:

	IV	=	57.5
5	SOS	=	33.5%
	N ₂₀	=	3.9%

Experimental details:

- 10 Volume crystalliser: 220 liter, 200 kg slurry present
stirrer speed: 4 rpm
cooling programme: 1 hour at 60°C
from 60 to 30 in 5 h
from 30 to 25 in 10 h
15 from 25 to 20 in 20 h
from 20 to 15 in 10 h
12 h at 15°C
from 15 to 14.4 in 5 h
- 20 Five pressings were done. The amounts of material removed per pressing are shown in the table below. After each removal the same amount of material was added to the crystalliser as a liquid at 14.4°C.
- 25 The volume of the press is variable between 10 and 50 liter. The press is of the membrane filterpress type.

Pressing profiles

- Pressings 1, 2 and 3 : 0-20 bar in 50 minutes (linear increase) followed by 10 minutes at 20 bar
30 Pressings 4 and 5: 0-24 bar in 50 minutes (linear increase) followed by 10 minutes at 24 bar

- Pressing temperature in all 5 pressings was the same as
35 the temperature in the crystalliser at the point in time when material was taken for the pressing. In this experiment: 14.4°C

	#1	#2	#3	#4	#5
Time (h)	0	4	24.5	28.5	46.5
S _C %	24.7	22.6	22.4	19.8	21.7
S _E %	21.8	21.8	21.8	21.8	21.8
σ	-0.13	-0.04	-0.03	0.09	0.005
weight of slurry removed /pressing kg	16.7	21.7	11.2	11.7	13.8
τ over 5 pressings h	3				
Sep. Eff of Press %	49.7	49.4	45.0	44.7	44.9
Yield of stearin %	45.8	41.4	52.0	53.5	50.9
Quality olein IV	65.5 8.4	63.9 12.0	64.9 9.0	63.6 11.0	67.4 7.0
N ₀					
Stearin	49.0	50.8	47.7	45.8	51.5
SOS (40h/20 °C N ₂₀)	49.9	54.1	43.9	46.4	46.7

Both olein and stearin are of acceptable quality.

CLAIMS

1. A process for the crystallisation of polymorphic fat molecules in a pseudo-steady state process, wherein the crystallisation is performed in a dry fractionation system in such a way that the crystal form of the product is a kinetically-stable crystal form, while during the crystallisation a σ -value is maintained below 0.5, preferably below 0.3, more preferably between 0.001 and 0.2, during a period of at least 12 hrs, wherein :

$$\sigma = 1 - \frac{S_c}{S_E}$$

- S_c being : percentage of solids in crystalliser at crystallisation temperature;
15 S_E being : percentage of solids after stabilisation for 48 hours at exit temperature of the crystalliser.

2. Process according to Claim 1, wherein the process is performed in a pseudo-steady state for at least 24 hours, preferably for at least 48 hours, more preferably for at least 60 hours.

3. Process according to Claims 1-2, wherein the residence time τ of the fat in the crystalliser is more than 1 hour, preferably more than 4 hours, more preferably more than 12 hours, τ being defined as :

$$\tau = \frac{\text{Volume of crystalliser}}{\text{Average flow rate}}$$

- 30 4. Process according to Claims 1-3, wherein a crystalliser is applied whose volume is more than 2 times, preferably more than 3 times, more preferably more than 5 times the volume of the separator applied.

- 35 5. Process according to Claim 4, wherein the volume of the crystalliser is more than 10 m³, preferably more than 30 m³, more preferably more than 60 m³.

6. Process according to Claims 1-5, wherein the fat is selected from the group consisting of palm oil, palm oil olein, shea, high-oleic sunflower oil, palm oil stearin, high stearic bean oil, hardened vegetable fat, enzymically
5 interesterified fats, chemically interesterified fats or mixtures thereof.

7. Process according to Claims 1-6, wherein the process is controlled by selecting and adjusting the flow rate,
10 shear rate and temperature only.

INTERNATIONAL SEARCH REPORT

In tional Application No
PCT/EP 95/03035

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 C11B7/00

According to International Patent Classification (IPC) or to both national classification and IPC.

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 C11B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched.

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP,A,0 535 475 (KRUPP MASCHINENTECHNIK) 7 April 1993 see page 4, column 5, line 51 - page 7, column 12, line 54 see examples 1-3 see claims 1-28	1-7
A	EP,A,0 262 113 (S.A. FRACTIONNEMENT TIRTIAUX) 30 March 1988 see claims 1-3	1-7
A	US,A,4 161 484 (HENDRIKUS J. VAN DEN BERG) 17 July 1979 see column 2, line 25 - column 3, line 21 see column 3, line 49 - column 4, line 62 see example 3	1-7
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

15 November 1995

Date of mailing of the international search report

24.11.95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl.
Fax: (+ 31-70) 340-3016

Authorized officer

Dekeirel, M

INTERNATIONAL SEARCH REPORT

Int ional Application No

PCT/EP 95/03035

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB,A,2 180 253 (ALFA-LAVAL FOOD & DAIRY ENGINEERING AB) 25 March 1987 see claims 1-9 ---	1-7
A	GB,A,2 270 925 (PALL CORPORATION) 30 March 1994 see page 19, line 34 - page 20, line 12 see claim 1 ---	1-7
A	REVUE FRANCAISE DES CORPS GRAS, vol. 21, no. 11, 1974 PARIS FR, pages 605-610, JAMES H. WHITTAM ET AL. 'Étude microscopique du vieillissement de la tripalmitine' see the whole document -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 95/03035

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-535475	07-04-93	DE-A- 4132892	22-04-93
		US-A- 5401867	28-03-95
EP-A-262113	30-03-88	LU-A- 86602	05-04-88
US-A-4161484	17-07-79	GB-A- 1580181	26-11-80
		AU-B- 508969	17-04-80
		AU-B- 2102377	13-07-78
		BE-A- 850088	04-07-77
		CA-A- 1099281	14-04-81
		DE-A- 2700302	14-07-77
		FR-A, B 2337759	05-08-77
		JP-C- 1284831	09-10-85
		JP-A- 52085207	15-07-77
		JP-B- 60004868	07-02-85
		LU-A- 76532	15-07-77
		NL-A- 7700106	12-07-77
		SE-B- 434275	16-07-84
		SE-A- 7700134	09-07-77
		SU-A- 1072814	07-02-84
GB-A-2180253	25-03-87	NONE	
GB-A-2270925	30-03-94	US-A- 5395531	07-03-95
		AU-B- 4206593	14-04-94
		BE-A- 1007448	04-07-95
		BR-A- 9303801	05-07-94
		CA-A- 2084578	29-03-94
		CN-A- 1101667	19-04-95
		DE-A- 4330256	31-03-94
		DK-A- 109593	29-03-94
		FR-A- 2696184	01-04-94
		JP-A- 6228588	16-08-94
		NL-A- 9301423	18-04-94
		SE-A- 9302819	29-03-94